
Collets

MR



page 199



Swiss quality MR collets

Type	Part no.	Ø		max. Shank tolerance
		[mm]	[inch]	
MR 11 [mm]				
Ø 1.0 mm	1111.01006	1.0	–	h11
Ø 2.0 mm	1111.02006	2.0	–	h11
Ø 3.0 mm	1111.03006	3.0	–	h11
Ø 4.0 mm	1111.04006	4.0	–	h11
Ø 5.0 mm	1111.05006	5.0	–	h11
Ø 6.0 mm	1111.06006	6.0	–	h11
MR 11 [inch]				
Ø 1/8"	1111.03186	3.175	1/8"	h11
Ø 3/16"	1111.04766	4.763	3/16"	h11
Ø 1/4"	1111.06356	6.35	1/4"	h11
MR 16 [mm]				
Ø 1.0 mm	1116.01006	1.0	–	h11
Ø 2.0 mm	1116.02006	2.0	–	h11
Ø 3.0 mm	1116.03006	3.0	–	h11
Ø 4.0 mm	1116.04006	4.0	–	h11
Ø 5.0 mm	1116.05006	5.0	–	h11
Ø 6.0 mm	1116.06006	6.0	–	h11
Ø 8.0 mm	1116.08006	8.0	–	h11
Ø 10.0 mm	1116.10006	10.0	–	h11
MR 16 [inch]				
Ø 1/8"	1116.03186	3.175	1/8"	h11
Ø 3/16"	1116.04766	4.763	3/16"	h11
Ø 1/4"	1116.06356	6.35	1/4"	h11
Ø 5/16"	1116.07946	7.938	5/16"	h11
Ø 3/8"	1116.09536	9.525	3/8"	h11

Expert advice

The micRun® MR collet represents the benchmark in precision: With a runout at (maximum) 2µm, it is the most accurate collet in the REGO-FIX lineup. MR collets are compatible with genuine REGO-FIX ER toolholders and increase the TIR of the entire system.

Type	Part no.	Ø [mm]	Ø [inch]	max. Shank tolerance
MR 25 [mm]				
Ø 1.0 mm	1125.01006	1.0	–	h11
Ø 2.0 mm	1125.02006	2.0	–	h11
Ø 3.0 mm	1125.03006	3.0	–	h11
Ø 4.0 mm	1125.04006	4.0	–	h11
Ø 5.0 mm	1125.05006	5.0	–	h11
Ø 6.0 mm	1125.06006	6.0	–	h11
Ø 8.0 mm	1125.08006	8.0	–	h11
Ø 10.0 mm	1125.10006	10.0	–	h11
Ø 12.0 mm	1125.12006	12.0	–	h11
Ø 14.0 mm	1125.14006	14.0	–	h11
Ø 16.0 mm	1125.16006	16.0	–	h11
MR 25 [inch]				
Ø 1/8"	1125.03186	3.175	1/8"	h11
Ø 1/4"	1125.06356	6.35	1/4"	h11
Ø 5/16"	1125.07946	7.938	5/16"	h11
Ø 3/8"	1125.09536	9.525	3/8"	h11
Ø 7/16"	1125.11116	11.113	7/16"	h11
Ø 1/2"	1125.12706	12.7	1/2"	h11
Ø 9/16"	1125.14296	14.288	9/16"	h11
Ø 5/8"	1125.15886	15.875	5/8"	h11
MR 32 [mm]				
Ø 2.0 mm	1132.02006	2.0	–	h11
Ø 3.0 mm	1132.03006	3.0	–	h11
Ø 4.0 mm	1132.04006	4.0	–	h11
Ø 5.0 mm	1132.05006	5.0	–	h11
Ø 6.0 mm	1132.06006	6.0	–	h11
Ø 8.0 mm	1132.08006	8.0	–	h11
Ø 10.0 mm	1132.10006	10.0	–	h11
Ø 12.0 mm	1132.12006	12.0	–	h11
Ø 14.0 mm	1132.14006	14.0	–	h11
Ø 16.0 mm	1132.16006	16.0	–	h11
Ø 18.0 mm	1132.18006	18.0	–	h11
Ø 20.0 mm	1132.20006	20.0	–	h11

Type	Part no.	Ø		max. Shank tolerance
		[mm]	[inch]	
MR 32 [inch]				
Ø 1/4"	1132.06356	6.35	1/4"	h11
Ø 5/16"	1132.07946	7.938	5/16"	h11
Ø 3/8"	1132.09536	9.525	3/8"	h11
Ø 7/16"	1132.11116	11.113	7/16"	h11
Ø 1/2"	1132.12706	12.7	1/2"	h11
Ø 9/16"	1132.14296	14.288	9/16"	h11
Ø 5/8"	1132.15886	15.875	5/8"	h11
Ø 11/16"	1132.17466	17.463	11/16"	h11
Ø 3/4"	1132.19056	19.05	3/4"	h11

